

SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: **Metabond Truck engine oil additive**

Version: 3 Latest revision: 15. 12. 2022 Previous version: 11. 07. 2018 Page: 1/(15)

SECTION 1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier:

Metabond Truck engine oil additive

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: engine oil additive with lubrication improvement and fraction-reducing effect for petrol-fuelled and diesel commercial vehicles, buses, mining equipments and agricultural machinery.

Uses advised against: application other than the above.

1.3 Details of the supplier of the safety data sheet:

Data of supplier:

Metabond Magyarország Kft.
9030 Győr, Szigligeti Ede u. 5.
Tel: +36 96 332738
Mobile: +36 70 2719575
www.metabond.hu

Responsible for SDS:

Metabond Magyarország Kft.
9030 Győr, Szigligeti Ede u. 5.
Tel: +36 96 332738
Mobile: +36 70 2719575
E-mail: metabond@metabond.hu
www.metabond.hu

1.4 Emergency telephone number

Emergency telephone (on workdays: 08-16 h (CET)): +36 96 332738

Health Toxicological Information Service (ETTSZ 1097 Budapest, Albert Flórián st. 2-6.)

Tel.: +36 80 201 199 (0-24 h, free number, can only be called from Hungary).

+36 1 476 6464 (0-24 h, can be called for a normal fee - also from abroad)

SECTION 2 Hazards identification

2.1 Classification of the substance or mixture

Hazard Class and Category:

Eye Irrit. 2

Aquatic Chronic 3

Hazard statement:

H319

H412

Causes serious eye irritation.

Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: **Metabond Truck engine oil additive**

Version: 3 Latest revision: 15. 12. 2022 Previous version: 11. 07. 2018 Page: 2/(15)

2.2 Label elements

Product identification: Trade name: **Metabond Truck engine oil additive**

Hazardous components: -

GHS Pictogram:



Signal word: **Warning**

Hazard statement:

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Supplemental hazard information:

EUH208 Contains N,N-bis(2-ethylhexyl)-((1,2,4-triazol-1-yl)methyl)amine. May produce an allergic reaction.

Precautionary statements – General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements – Prevention:

P273 Avoid release to the environment.

P280 Wear protective gloves, eye protection.

Precautionary statements – Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

Precautionary statements – Storage: -

Precautionary statements – Disposal:

P501 Dispose of contents/container in accordance with national regulation.

Other liabilities for labelling:

Tactile warning of danger: Not required.

Transport classification: see section 14.

2.3 Other hazards

The product does not contain any PBT or vPvB substance according to annex XIII of regulation (EC) 1907/2006, at a concentration of 0.1% or more.

SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: **Metabond Truck engine oil additive**

Version: 3 Latest revision: 15. 12. 2022 Previous version: 11. 07. 2018 Page: 3/(15)

The product contains an endocrine disrupting ingredient: Phenol, dodecyl-, branched (CAS: 121158-58-5)
Endocrine disrupting properties (Article 57(f) - human health);
Endocrine disrupting properties (Article 57(f) - environment).

SECTION 3 Composition/information on ingredients

3.2 Mixtures

Chemical description: A mixture of mineral oil, synthetic oil and additives.

Component(s) / Hazardous component(s):

Name	EC number	CAS number	Hazard classes and cat.	Hazard statements	Conc. %(m/m)
Mineral oil * REACH Registr. Nr.: no data	-	-	Asp. Tox. 1	H304	max. 30
4,4'-methylene bis (dibutyldithiocarbamate) REACH Registr. Nr.: 01-2119708416-41	233-593-1	10254-57-6	Aquatic Chronic 4	H413	max. 15
Calcium branched alkyl phenate sulphide REACH Registr. Nr.: no data	-	polymer	Aquatic Chronic 4	H413	max. 3.0
Zinc dialkyl dithiophosphate** REACH Registr. Nr.: 01-2119953275-34	218-679-9	2215-35-2	Skin Irrit. 2 Eye Dam. 1 Aquatic Chronic 2	H315 H318 H411	max. 2.0
Butanedioic acid, 2,3- dihydroxy-, mixed C12- C16-alkyl and C13rich, C11-C14 isoalkyl diesters REACH Registr.Nr.: 01-0000020152-85	482-100-8	-	Eye Dam. 1	H318	max. 2.0
2,6-di-tert-butylphenol REACH Registr. Nr.: 01-2119490822-33	204-884-0	128-39-2	Skin Irrit. 2 Aquatic Acute 1 Aquatic Chronic 1	H315 H400 (M=1) H410 (M=1)	max. 0.6
Phenol, dodecyl-, branched REACH Registr. Nr.: 01-2119513207-49	310-154-3	-	Eye Dam. 1 Skin Corr. 1C Repr. 1B Aquatic Acute 1 Aquatic Chronic 1	H318 H314 H360F H400 (M=10) H410 (M=10)	max. 0.15

SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: **Metabond Truck engine oil additive**

Version: 3 Latest revision: 15. 12. 2022 Previous version: 11. 07. 2018 Page: 4/(15)

Name	EC number	CAS number	Hazard classes and cat.	Hazard statements	Conc. %(m/m)
N,N-bis(2-ethylhexyl)-((1,2,4-triazol-1-yl)methyl)amine (Additive) REACH Registr. Nr.: 01-2119930450-49	401-280-0	91273-04-0	Skin Corr. 1B Skin Sens. 1A Eye Dam. 1 Aquatic Chronic 1	H314 H317 H318 H410	max. 0.06

*Contains one or more of the following:

EC number: 265-157-1, REACH Registr. Nr.: 01-2119484627-25;

EC number: 265-169-7, REACH Registr. Nr.: 01-2119471299-27;

EC number: 265-158-7, REACH Registr. Nr.: 01-2119487077-29;

EC number: 265-159-2, REACH Registr. Nr.: 01-2119480132-48.

**Specific concentration limit: Eye Dam. 1, H318: ≥ 10 %

Note L:

The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.

The full text of each relevant H- phrase and Hazard classes and cat. see in Section 16.

SECTION 4 First aid measures

4.1 Description of first aid measures

General information: Never give anything by mouth to an unconscious person, or never induce vomiting.

Inhalation: Remove the affected person to fresh air. If rapid recovery does not occur, obtain medical attention.

Skin contact: Remove contaminated clothing. Wash skin with large amounts of water, use soap. In case of persistent irritation, get medical attention.

Eye contact: In case of contact, immediately flush eyes with plenty of water for at least 10-15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of a complaint, seek medical advice.

Ingestion: If swallowed, give water. **Do not** induce vomiting. Get medical attention.

Protection of first-aid person: No individual specifications.

SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: **Metabond Truck engine oil additive**

Version: 3 Latest revision: 15. 12. 2022 Previous version: 11. 07. 2018 Page: 5/(15)

- 4.2 Most important symptoms and effects, both acute and delayed
Prolonged and/or repeated contact may cause irritation on skin depending on individual sensitivity.
Causes serious eye irritation.
May produce an allergic reaction.
- 4.3 Indication of any immediate medical attention and special treatment needed
Not required.

SECTION 5 Fire-fighting measures

Fire hazards:
Combustible.

5.1 Extinguishing media

Suitable extinguishing media:

Foam, carbon dioxide, dry chemical powder, water spray.

Unsuitable extinguishing media:

Full water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products:

On burning, carbon monoxide, carbon dioxide, various hydrocarbons and soot can be formed.

5.3 Advice for fire-fighters

Special protective equipment:

According to the existing fire-fighting regulations. Respiratory protection.

Further information:

Collect contaminated firefighting water separately. It must not enter the sewage system.

Contaminated extinguishing water must be disposed of in accordance with official regulations.

SECTION 6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: see Section 8.

Danger of slipping on leaked out/spilled product.

6.2 Environmental precautions:

Confine spills to prevent material from entering sewers, watercourses, drains and into soil

Notify relevant authority.

SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: **Metabond Truck engine oil additive**

Version: 3 Latest revision: 15. 12. 2022 Previous version: 11. 07. 2018 Page: 6/(15)

6.3 Methods and material for containment and cleaning up

On soil: All kind of ignition sources should be removed. Contain spilled liquid with sand, earth or other suitable absorbents. Recover free liquid by pumping. Dispose of according to local regulations.

On water: Confine the spillage. Remove from surface by skimming or suitable absorbents. Notify local authorities according to regulations.

6.4 Reference to other sections

Personal precautions: see section 8.

Waste treatment methods: see section 13.

SECTION 7 Handling and storage

7.1 Precautions for safe handling

Keep general measures applied for normal operations with lubricants.

Keep away from radiant heat and open flame.

Avoid contact with skin and eyes. Avoid prolonged breathing of oil vapours or mists.

Wash hands before breaks and at end of work.

Take off contaminated clothing and wash it before reuse.

When using do not eat, drink or smoke. Avoid splashing the product.

Handling temperature: not known.

7.2 Conditions for safe storage, including any incompatibilities

Storage facilities must comply with regulations for storing of flammable liquids.

Store in dry, well-ventilated place in original, closed containers.

Keep away from radiant heat, open flame and strong oxidizing agents.

Storage temperature: max. 40°C.

7.3 Specific end use(s)

Engine oil additive with lubrication improvement and fraction-reducing effect for petrol-fuelled and diesel commercial vehicles, buses, mining equipments and agricultural machinery.

SECTION 8 Exposure controls / personal protection

8.1 Control parameters:

Mineral oil mist: TWA: **5 mg/m³**; STEL: 10 mg/m³, for oil mist, vapour excluded (ACGIH).

Method of testing, recommended: NIOSH 5026

SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: **Metabond Truck engine oil additive**

Version: 3 Latest revision: 15. 12. 2022 Previous version: 11. 07. 2018 Page: 7/(15)

8.2 Exposure controls

Engineering control measures:

Not required.

Personal protection:

- | | |
|----------------------------|--|
| (a) Eye/face protection | Protective goggles, if splashes may occur (EN 166). |
| (b) Skin protection | |
| (i) Hand protection | Oil resistant gloves (EN 374, Breakthrough time > 480 min, PK power level: 6; PR flow rate: 0).
Note: Manufacturer's directions for use and the conditions of application should be observed. |
| (ii) Other | Protective clothing (oil resistant). |
| (c) Respiratory protection | Under normal conditions not required. In case of vapor formation respiratory protection with particle-filter is recommended. |
| (d) Thermal hazards | No data. |

Environmental exposure controls:

Do not discharge into drains/surface waters/groundwater.

SECTION 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|--|---|
| a) Physical state: | liquid |
| b) Colour: | brown, bright |
| c) Odour: | characteristic, not unpleasant |
| d) Melting point/freezing point (Pour point): | not available |
| e) Boiling point or initial boiling point and boiling range: | not available |
| f) Flammability: | combustible |
| g) Lower and upper explosion limit: | not explosive |
| h) Flash point (COC) (EN ISO 2592): | typ. 170°C |
| i) Auto-ignition temperature: | not available |
| j) Decomposition temperature: | not available |
| k) pH: | not applicable |
| l) Kinematic viscosity | |
| | at 40°C: typ. 283.3 mm ² /s (DIN 51562) |
| | at 100°C: not available |

SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: **Metabond Truck engine oil additive**

Version: 3 Latest revision: 15. 12. 2022 Previous version: 11. 07. 2018 Page: 8/(15)

- m) Solubility
Solubility in water: practically insoluble in water
Solubility in other solvents: gasoline, kerosene, toluene, etc.
- n) Partition coefficient n-octanol/water (log value): not available
- o) Vapour pressure at 20°C: negligible
- p) Density and/or relative density at 20°C (DIN 51757): 0.975 g/cm³
- q) Relative vapour density: not available
- r) Particle characteristics: not available

9.2 Other information
not available

SECTION 10 Stability and reactivity

- 10.1 Reactivity: Dangerous reactivity not known.
- 10.2 Chemical stability: No decomposition if stored and handled properly.
- 10.3 Possibility of hazardous reactions: Not known.
- 10.4 Conditions to avoid: Direct heat or ignition sources.
- 10.5 Incompatible materials: Strong oxidizing agents.
- 10.6 Hazardous decomposition products: No dangerous decomposition products are formed under normal conditions. Hazardous combustion products: See Section 5.

SECTION 11 Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Based on available data, the classification criteria are not met.

Components:

4,4'-methylene bis (dibutyldithiocarbamate) (CAS: 10254-57-6):

Oral:	LD ₅₀ (rat)	16 000 mg/kg	OECD 401
Dermal:	LD ₅₀ (rabbit)	> 2 000 mg/kg	OECD 402

- Skin corrosion/irritation: Based on available data, the classification criteria are not met.
- Serious eye damage/irritation: Causes serious eye irritation.
- Respiratory or skin sensitisation: Based on available data, the classification criteria are not met.
- Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- Carcinogenicity: Based on available data, the classification criteria are not met.
- Reproductive toxicity: Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: **Metabond Truck engine oil additive**

Version: 3 Latest revision: 15. 12. 2022 Previous version: 11. 07. 2018 Page: 10/(15)

Daphnia (<i>Daphnia magna</i>):	EC ₅₀	23 mg/l	48 h
Daphnia (<i>Daphnia magna</i>):	NOEC	0.4 mg/l	21 days
Algae (<i>Scenedesmus quadricauda</i>):	EC ₅₀	21 mg/l	72 h
Microorganisms:	EC ₅₀	> 10 000 mg/l	0.1 days

2,6-di-tert-butylphenol (CAS: 128-39-2):

Fish (<i>Oncorhynchus mykiss</i>):	LC ₅₀	13 mg/l	96 h
Fish (<i>Cyprinus carpio</i>):	LC ₅₀	1.4 mg/l	96 h
Daphnia (<i>Daphnia magna</i>):	EC ₅₀	0.45 mg/l	48 h
Daphnia (<i>Daphnia magna</i>):	EC ₅₀	0.8 mg/l	48 h
Algae (<i>Selenastrum capricornutum</i>):	EC ₅₀	3.6 mg/l	72 h
Microorganisms:	EC ₅₀	> 1 000 mg/l	0.1 days

Phenol, dodecyl-, branched (EC: 310-154-3)

Fish (Fat-headed carp):	LC ₅₀	40 mg/l	96 h
Daphnia magna:	EC ₅₀	0.037 mg/l	48 h
Mysidopsis Bahia:	EC ₅₀	> 0.58 mg/l	96 h
Daphnia magna:	EC ₅₀	0.0079 mg/l	21 days
Daphnia magna:	NOEC	0.0037 mg/l	21 days
Algae (<i>Scenedesmus quadricauda</i>):	EC ₅₀	0.36 mg/l	72 h
Microorganisms:	EC ₅₀	> 1 000 mg/l	0.1 days

12.2 Persistence and degradability

Biodegradability: Hydrocarbons are inherently degradable.

4,4'-methylene bis

(*dibutyldithiocarbamate*) (CAS: 10254-57-

6) Not easily degradable.

Mineral oil (CAS: -) 31% (28 days, OECD TG 301 B)

Not easily degradable.

Calcium branched alkyl phenate sulphide

(*overbased*) (CAS: -) 4.7 – 10.8% (28 days, OECD TG 301 B).

Not easily degradable.

Inherent sedimentation: 38.8% (28 days)

Zinc dialkyl dithiophosphate (CAS: 2215-

35-2): 1.5% (28 days, OECD TG 301 B)

Not easily degradable.

2,6-di-tert-butylphenol (CAS: 128-39-2) 24% (28 days, OECD 302 B)

Not easily degradable.

5% (28 days, OECD 301 B)

Not easily degradable.

SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: **Metabond Truck engine oil additive**

Version: 3 Latest revision: 15. 12. 2022 Previous version: 11. 07. 2018 Page: 11/(15)

<i>Phenol, dodecyl-, branched (EC: 310-154-3)</i>	Mixed: 10% (56 days, OECD TG 301 B) Not easily degradable. 25% (28 days, OECD TG 301 B) Not easily degradable.
12.3 Bioaccumulative potential	No data available.
<i>4,4'-methylene bis (dibutyldithiocarbamate) (CAS: 10254-57-6)</i>	Log Pow: 8.42 BCF: 10.86 (low potential)
<i>Calcium branched alkyl phenate sulphide (overbased) (CAS: -)</i>	BCF: 2.2; Log Kow: 11.08 (measured value)
<i>Zinc dialkyl dithiophosphate (CAS: 2215-35-2):</i>	Log Kow: 2.21 (measured value, 20 °C)
<i>2,6-di-tert-butylphenol (CAS: 128-39-2)</i>	BCF: 794.33 (measured value)
<i>Phenol, dodecyl-, branched (EC: 310-154-3)</i>	Log Kow: 7.14 (measured value)
12.4 Mobility in soil	Absorbs in soil.
Mobility in water:	Floats on water.
12.5 Results of PBT and vPvB assessment	Does not contain PBT and vPvB substances, at a concentration of 0.1% or more.
12.6 Endocrine disrupting properties	The product contains an endocrine disrupting ingredient: Phenol, dodecyl-, branched (CAS: 121158-58-5) Endocrine disrupting properties (Article 57(f) - environment).
12.7 Other adverse effects	
Heavy metal content:	None.
PCT, PCB and other chlorinated hydrocarbons:	None.
Environmental effects:	Large spills may be hazardous to the environment.
Water hazard class (German):	WGK 2 (Classification by AwSV)

SECTION 13 Disposal considerations

13.1 Waste treatment methods

Product disposal:

Wastes of the product or used oil should be treated as hazardous waste.

SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: **Metabond Truck engine oil additive**

Version: 3 Latest revision: 15. 12. 2022 Previous version: 11. 07. 2018 Page: 13/(15)

15.2 Chemical safety assessment.
not available

SECTION 16 Other information

The information given in this data sheet is based on our best knowledge at the time of publication. The information is related only to this product and is intended to assist its safe transport, handling and use. The given physical and chemical parameters describe the product only for the purpose of safety requirements and therefore should not be construed as guaranteeing any specific property of the product or as being part of a product specification or any contract.

The manufacturer or supplier shall not take responsibility for any damages from the use other than recommended or other misuse of the product. It is the responsibility of the user to keep regulatory precautions and observe recommendations for safe use of the product.

Classification for mixtures and used evaluation method according to regulation 1272/2008/EC (CLP)

Eye Irrit. 2	H319	calculation method
Aquatic Chronic 3	H412	calculation method

The full text of each relevant H- phrase and Hazard classes and cat. in Section 3.:

H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H360F	May damage fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
Asp. Tox. 1	Aspiration hazard Category 1
Skin Corr. 1C, 1B	Skin corrosion/irritation Category 1C, 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1A	Respiratory/skin sensitization Category 1A
Eye Dam. 1	Serious eye damage/eye irritation Category 1

SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: **Metabond Truck engine oil additive**

Version: 3 Latest revision: 15. 12. 2022 Previous version: 11. 07. 2018 Page: 14/(15)

Repr. 1B	Reproductive toxicity Category 1B
Aquatic Acute 1	Hazardous to the aquatic environment, Acute Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, Chronic Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, Chronic Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment, Chronic Category 4

Legend:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BOD	Biological Oxygen Demand
Bw	Body Weight
C&L	Classification and Labelling
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic or toxic to Reproduction
COD	Chemical Oxygen Demand
CSA	Chemical Safety Assessment
CSR	Chemical Safety Report
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
ECHA	European Chemicals Agency
Ec _x	Effective Concentration x%
ErC ₅₀	EC ₅₀ in terms of reduction of growth rate
Ed _x	Effective Dose x%
EC	European Community
EC number	European Community number
ELINCS	European List of Notified Chemical Substances
ES	Exposure Scenario
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC _x	Lethal Concentration x%
LD _x	Lethal Dose x%
LOAEC	Lowest Observed Adverse Effect Concentration
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
NOEC	No observed effect concentration
NOEL	No observed effect level
NLP	No-Longer Polymer
NOAEL	No Observed Adverse Effect Level

SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: **Metabond Truck engine oil additive**

Version: 3 Latest revision: 15. 12. 2022 Previous version: 11. 07. 2018 Page: 15/(15)

OECD	Organisation for Economic Cooperation and Development
PBT	Persistent Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	parts/million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International carriage of Dangerous Goods by Rail
SVHC	Substance of Very High Concern
UVCB	substance of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bio-accumulative

Revision Indicators:

Section	Subject of change	Date	Version
1-16	Revision modification according to 2020/878/EU Full revision due to composition change	15. 12. 2022	3